

Report No.:

Test Time: 2021-04-13 14:26

Luminaire Property

Luminaire Manufacturer:

Luminaire Category: A17041-3000K

Lamp Description: 2835

Current: 0.154 A

Power Factor: 0.945

Lamp Catalog: LED

Voltage: 120.0 V

Power: 17.50 W

Photometric Results

CIE Class: Direct

Measurement Flux: 1080.2 lm

Downward Ratio: 96%

Field Angle(C0/C180,C90/C270,C45/C225,C135/315): 165.1, 165.3, 165.2, 165.2

Beam Angle(C0/C180,C90/C270,C45/C225,C135/315): 112.8, 112.8, 112.8, 112.8

Luminaire Efficacy Rating (LER): 61.77

Max. Intensity: 356.93 cd

S/MH(C0/C180): 1.25

Total Rated Lamp Lumens: 1080.2 lm

Efficiency: 100%


Upward Ratio: 4%

Central Intensity: 356.92 cd


Pos of Max. Intensity: H0 V2

S/MH(C90/C270): 1.25

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator: SUSHUNHUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 7.344 m

Humidity:

Inspector:


Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	118	118	118	118	115	115	115	115	109	109	109	103	103	103	98	98	98	96
1	107	102	98	94	104	100	96	92	95	91	88	90	87	85	86	84	82	79
2	97	89	82	76	94	87	80	75	82	77	72	79	74	70	75	71	68	66
3	89	78	70	63	86	76	68	62	72	66	61	69	64	59	66	61	57	55
4	81	69	60	53	78	67	59	53	64	57	51	61	55	50	59	54	49	47
5	75	62	52	46	72	60	52	45	58	50	44	55	49	44	53	47	43	40
6	69	55	46	40	67	54	46	39	52	44	39	50	43	38	48	42	38	35
7	64	50	41	35	62	49	41	35	47	40	34	45	39	34	44	38	33	31
8	59	46	37	31	58	45	37	31	43	36	31	42	35	30	40	34	30	28
9	55	42	34	28	54	41	33	28	40	33	28	38	32	27	37	31	27	25
10	52	39	31	25	50	38	30	25	37	30	25	36	29	25	34	29	24	23

Spacing Criteria (0-180): 1.25

Spacing Criteria (90-270): 1.25

Spacing Criteria (Diagonal): 1.37



C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator: SUSHUNHUA

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1600L

Distance: 7.344 m

Humidity:

Inspector:

IsoLux Plot



Mounting Height: 10.0m		Max Lux(100%): 3.6 lx	
— (5%):	0.2 lx	— (15%):	0.5 lx
— (25%):	0.9 lx	— (35%):	1.2 lx
— (45%):	1.6 lx	— (55%):	2.0 lx
— (65%):	2.3 lx		

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator: SUSHUNHUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 7.344 m



Humidity:

Inspector:

Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300

a b c d e f g h



L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	242	218	191	164	136	107	79	52	29
C90	231	206	180	152	124	96	69	44	24
C180	233	208	181	153	124	95	68	42	22
C270	241	217	191	163	135	106	77	51	28

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator: SUSHUNHUA

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1600L

Distance: 7.344 m


Humidity:

Inspector:

Illuminance at a Distance



Vertical IsoLux Plot




Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 356.9 lx

(5%): 17.8 lx	(15%): 53.5 lx
(25%): 89.2 lx	(35%): 124.9 lx
(45%): 160.6 lx	(55%): 196.3 lx
(65%): 232.0 lx	

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator: SUSHUNHUA

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 7.344 m
Humidity:
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM

	ZONE	LUMENS	% LAMP LUMENS
	FORWARD LIGHT	512	47.4
	FL (0°-30°)	137	12.7
	FM (30°-60°)	259	24.0
	FH (60°-80°)	101	9.3
	FVH (80°-90°)	14	1.3
	BACK LIGHT	524	48.5
	BL (0°-30°)	138	12.8
	BM (30°-60°)	265	24.5
	BH (60°-80°)	105	9.8
	BVH (80°-90°)	15	1.4
	UP LIGHT	44	4.1
	UL (90°-100°)	7	0.6
	UH (100°-180°)	38	3.5
	TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B1 U2 G1
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B1 U2 G1

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator: SUSHUNHUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 7.344 m

Humidity:

Inspector: