

Report No.:

Test Time: 2021-04-15 16:31

Luminaire Property

Luminaire Manufacturer:

Luminaire Category: A17049-5000K

Lamp Description: 2835

Current: 0.237 A

Power Factor: 0.946

Lamp Catalog: LED

Voltage: 120.1 V

Power: 26.95 W

Photometric Results

CIE Class: Direct

Measurement Flux: 1851.4 lm

Downward Ratio: 96%

Field Angle(C0/C180,C90/C270,C45/C225,C135/315): 165.1, 164.8, 164.9, 164.9

Beam Angle(C0/C180,C90/C270,C45/C225,C135/315): 113.4, 113.2, 113.3, 113.3

Luminaire Efficacy Rating (LER): 68.75

Max. Intensity: 608.11 cd

S/MH(C0/C180): 1.26

Total Rated Lamp Lumens: 1851.4 lm

Efficiency: 100%

Upward Ratio: 4%

Central Intensity: 608.05 cd


Pos of Max. Intensity: H180 V1

S/MH(C90/C270): 1.26

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator: SUSHUNHUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 7.344 m

Humidity:

Inspector:


Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	118	118	118	118	115	115	115	115	109	109	109	103	103	103	98	98	98	96
1	107	102	98	94	104	100	96	92	95	91	88	90	87	85	86	84	82	79
2	97	89	82	76	94	87	80	75	82	77	72	79	74	70	75	71	68	66
3	89	78	70	63	86	76	68	62	72	66	61	69	64	59	66	61	57	55
4	81	69	60	53	78	67	59	53	64	57	51	61	55	50	59	54	49	47
5	75	62	52	46	72	60	52	45	58	50	44	55	49	44	53	47	43	40
6	69	55	46	40	67	54	46	39	52	44	39	50	43	38	48	42	37	35
7	64	50	41	35	62	49	41	35	47	40	34	45	39	34	44	38	33	31
8	59	46	37	31	57	45	37	31	43	36	31	42	35	30	40	34	30	28
9	55	42	34	28	54	41	33	28	40	33	28	38	32	27	37	31	27	25
10	52	39	31	25	50	38	30	25	37	30	25	35	29	25	34	29	24	23

Spacing Criteria (0-180): 1.26

Spacing Criteria (90-270): 1.26

Spacing Criteria (Diagonal): 1.38



C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator: SUSHUNHUA

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1600L

Distance: 7.344 m

Humidity:

Inspector:

IsoLux Plot



Mounting Height: 10.0m		Max Lux(100%): 6.1 lx	
(5%):	0.3 lx	(15%):	0.9 lx
(25%):	1.5 lx	(35%):	2.1 lx
(45%):	2.7 lx	(55%):	3.3 lx
(65%):	4.0 lx		

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator: SUSHUNHUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 7.344 m


Humidity:

Inspector:

Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300

a b c d e f g h



L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	398	355	310	263	214	166	118	75	40
C90	403	360	314	267	218	169	121	77	41
C180	417	376	330	283	233	182	132	86	47
C270	408	366	321	274	225	175	127	82	44

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator: SUSHUNHUA

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-1600L

Distance: 7.344 m


Humidity:

Inspector:

Illuminance at a Distance



Vertical IsoLux Plot




Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 608.0 lx

(5%): 30.4 lx	(15%): 91.2 lx
(25%): 152.0 lx	(35%): 212.8 lx
(45%): 273.6 lx	(55%): 334.4 lx
(65%): 395.2 lx	

C Plane (°):0.0-360.0: 90.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator: SUSHUNHUA

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-1600L
Distance: 7.344 m
Humidity:
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM

	ZONE	LUMENS	% LAMP LUMENS
	FORWARD LIGHT	883	47.7
	FL (0°-30°)	235	12.7
	FM (30°-60°)	448	24.2
	FH (60°-80°)	175	9.4
	FVH (80°-90°)	24	1.3
	BACK LIGHT	891	48.1
	BL (0°-30°)	236	12.8
	BM (30°-60°)	452	24.4
	BH (60°-80°)	178	9.6
	BVH (80°-90°)	25	1.4
	UP LIGHT	78	4.2
	UL (90°-100°)	12	0.6
	UH (100°-180°)	66	3.6
	TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B1 U2 G1
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B1 U2 G1

C Plane (°):0.0-360.0: 90.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator: SUSHUNHUA

Gamma Plane (°):0.0-180.0:1.0

Test Device: GPM-1600L

Distance: 7.344 m

Humidity:

Inspector: